

#### AL175ULB

# Switching Power Supply/Charger Board

Altronix AL175ULB power-limited power supply/charger converts a 24VAC input into two (2) individual PTC protected auto-resettable 12VDC or 24VDC outputs. It is intended for use in applications requiring UL Listing for Access Control (UL294) and applications requiring an interface with Fire Alarm Control Panels.



## Specifications

Input

Voltage 24VAC/40VA. Class 2 transformer Trigger Access control trigger input

Outputs

Two (2) Class 2 Rated power-limited outputs
- Fail-Safe/Fail-Secure lock output (switched)

- Auxiliary power output (unswitched)

Voltage 12VDC or 24VDC selectable

Current 12VDC @ 1.75A or

24VDC @ 0.9A continuous max

Other Short circuit and thermal overload protection

**Battery Charging** 

Type Sealed lead acid or gel type
Failover Upon AC loss, instantaneous

Batteries are sold separately

Fire Alarm Disconnect

Supervised Latching or non-latching

Supervision

AC Failure Form "C" contacts

Indicators (LED)

Input Input voltage is present

DC Output Powered

**Agency Listings** 

UL294 Access Control

Physical and Environmental

Dimensions (L x W x H)

Board: 5.8" x 3.0" x 1.5" (147.3mm x 76.2mm x 38.1mm)

Shipping: 8" x 6" x 5" (203.2mm x 152.4mm x 127mm)

Weight (approx.)

Product Weight: 0.35 lb. (0.16 kg) Shipping Weight: 0.5 lb. (0.23 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
Storage: -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/- 5% BTU/Hr (approx.): 11 BTU/Hr.



## AL175ULB

Switching Power Supply/Charger Board

#### Dimensions and Drawing -

Board Dimensions (L x W x H approximate)

5.8" x 3.0" x 1.5" (147.3mm x 76.2mm x 38.1mm)

Mounting Holes' Tolerance: +/- 0.04 in. (1mm)

